



## eni Rotra ATF III

eni Rotra ATF III provides the performances required to meet GM Dexron III G, Ford Mercon, Allison C4 specifications and other main European OEM specifications.

### CHARACTERISTICS (TYPICAL FIGURES)

#### eni Rotra ATF III

Viscosity at 100°C	mm <sup>2</sup> /s	7,7
Viscosity at -40°C	mPa.s	18000
Viscosity Index	-	200
Flash Point COC	°C	200
Pour Point	°C	-48
Colour	-	red
Mass Density at 15°C	kg/l	0,862

### PROPERTIES AND PERFORMANCE

- Excellent oxidation stability, resulting in cleaner transmissions and more reliable operation.
- Stable friction properties, as demonstrated in cycling test and friction durability tests.
- Excellent low temperature fluidity.
- Compatibility with a wide range of elastomers and metals, providing protection against wear and risks of leakages.

### SPECIFICATIONS

eni Rotra ATF III is officially approved or meets the requirements of the following specifications:

- GM DEXRON III G
- Ford MERCON
- Allison C4
- M.B. 236.1
- MAN 339 type Z-1 level
- MAN 339 type V-1 level
- Voith 55.6335 (G 607, DIWA e MINIMAT transmissions)
- ZF TE-ML 04D, 11B, 14A
- Volvo 97341