



AGIP BLASIA SX

AGIP BLASIA SX is an oil developed for the lubrication of gears and bearings operating at high temperatures. It is formulated from a synthetic base (polyalphaolefin) additive-treated to impart appropriate antirust, antiwear properties and exceptional oxidation and thermal stability.

CHARACTERISTICS (TYPICAL FIGURES)

| AGIP BLASIA SX | | 100 | 150 | 220 | 320 |
|----------------------|--------------------|-------|-------|-------|-------|
| Viscosity at 40°C | mm ² /s | 95,8 | 148,7 | 220 | 316 |
| Viscosity at 100°C | mm ² /s | 13,14 | 18,5 | 23,8 | 31,0 |
| Viscosity Index | - | 135 | 140 | 135 | 135 |
| Flash Point COC | °C | 250 | 250 | 250 | 250 |
| Pour Point | °C | -33 | -48 | -33 | -33 |
| Mass density at 15°C | kg/l | 0,850 | 0,845 | 0,850 | 0,850 |

PROPERTIES AND PERFORMANCE

- AGIP BLASIA SX is formulated from a base with inherently good lubricating capacity. The very high Viscosity Index minimizes change in viscosity over a wide range of operating temperatures.
- It has exceptional oxidation and thermal stability. The additives have been selected to avoid the formation of sludge even if a small part of the fluid oxidizes owing to extreme working conditions.
- AGIP BLASIA SX has very good antiwear properties as illustrated by FZG test (12+ stage pass)
- It provides very good protection against rust and corrosion.

APPLICATIONS

AGIP BLASIA SX is best used for the lubrication of bearings of marine separators, gears operating at high temperatures (glassforming machines, steelstrip mills, furnaces and ceramic and paper-making machinery). Suitable for continuous bulk temperatures up to 120 °C with peaks in the hottest points up to 200 °C.

SPECIFICATIONS

AGIP BLASIA SX oils meet the requirements of the following specifications:

- ISO 6743-6/CKT
- ANSI-AGMA 9005 D94, AGMA NO. 3S, NO. 5S, NO. 6S
- DIN 51517 T.3/CLP 100, 220, 320

AGIP BLASIA SX 320 is approved by Alfa Laval